

empackEmpack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571**PRODUCT: Emzone G21 Corrosion Guard - 400g****CODE: 045021****Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Identity..... Emzone G21 Corrosion Guard - 400g
 Product Item Numbers..... 045021
 Manufactured by..... Empack Spraytech Inc.
 98 Walker Drive
 Brampton
 Ontario
 Canada
 L6T 4H6
 905-792-6571
 24 hour emergency telephone number..... CANUTEC: (613)-996-6666 collect.
 Recommended Use..... Multi-purpose lubricant and rust inhibitor .
 Consumer Commodity..... Yes.
 Hazard Ratings:
 HMIS..... Health: 1 Fire: 3 Reactivity: 1.
 NFPA Rating..... Health: 1 Fire: 3 Reactivity: 1.

Section 02: HAZARDS IDENTIFICATION

Emergency Overview..... Extremely flammable . Container is under pressure. May catch fire. Container may explode if heated. Do not puncture. Do not burn. Do not get in eyes or clothing. Do not breathe fumes. KEEP OUT OF REACH OF CHILDREN .

Potential Health Effects:
 Eye Contact..... May cause irritation, redness and pain.
 Skin Contact..... Can cause skin irritation. Prolonged or repeated contact may dry the skin.
 Ingestion..... Ingestion may cause headache, nausea, vomiting and weakness.
 Inhalation..... Inhalation of vapour may cause irritation.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
Petroleum Hydrocarbons	64742-80-0	60-100
Propane	74-98-6	10-30
Isobutane	75-28-5	10-30

Section 04: FIRST AID MEASURES

Eye Contact..... Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation persists.
 Skin Contact..... If irritation or redness develops, seek medical attention. Wash exposed area with soap and water.
 Ingestion..... Not applicable - Product is a gas at ambient temp.
 Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. If breathing is difficult, give oxygen and get medical attention. Do not give adrenaline, epinephrine or similar drugs following exposure to this product.
 Additional Information..... Note to the doctor; treat symptomatically.

Section 05: FIRE FIGHTING MEASURES

Flammability Class..... Extremely Flammable.
 Extinguishing Media..... Carbon dioxide, dry chemicals, foam or water fog.
 Sensitivity to Mechanical Impact..... Not expected to be sensitive.
 Sensitivity to Static Discharge..... Not expected to be sensitive.

Section 06: ACCIDENTAL RELEASE MEASURES

Spills and Leaks..... Large spill or leak is unlikely in aerosol containers. If spill or leak occurs, ventilate enclosed spaces and disperse gas with floor-level forced-air ventilation. Exhaust vapours outdoors. Do not smoke or operate internal combustion engines. Remove flames and heating elements.

PRODUCT: Emzone G21 Corrosion Guard - 400g

CODE: 045021

Section 07: HANDLING AND STORAGE

Handling..... Use with adequate ventilation. Do not enter confined spaces unless adequately ventilated.
Do not store in temperatures above 120°F (50°C).

Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye/Type..... Use chemical safety glasses.
Skin/Type..... Use gloves and protective clothing against cold temperature made from viton, butyl rubber,
PVC, neoprene or nitrile.
Respiratory/Type..... Not required on a short-term basis or if exhaust ventilation is provided. Use approved
NIOSH respirators for emergencies.
Engineering Controls..... Local exhaust ventilation required to maintain the point of use below the Threshold Limit
Value if unprotected personnel are involved.

Exposure Limits

Ingredients	TWA	ACGIH TLV		PEL	OSHA PEL		REL	NIOSH
		STEL			STEL			
Petroleum Hydrocarbons	Not available	Not available	Not available	Not available	Not available	Not available	Not available	Not available
Propane	2,500 ppm	Not available	Not available	1,000 ppm	Not available	Not available	1,000 ppm	1,000 ppm
Isobutane	800 ppm	1000 ppm	1000 ppm	800ppm	Not available	Not available	800 ppm (TWA)	800 ppm (TWA)

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State..... Aerosol.
Physical Appearance..... Dark oil mist.
Odour..... Odourless.
Odour Threshold (ppm)..... Not available.
pH..... Not applicable.
Vapour Pressure (psig)..... 80- 95 .
Vapour Density (Air=1)..... Not available.
Evaporation Rate (n-Butyl Acetate = 1)..... > 1 .
Initial Boiling Point/Boiling Range (° C)..... 140°C- 150°C.
VOC Content..... 95-100 % wt.
Specific Gravity (Liquid)..... 0.850- 0.920.
Specific Gravity (Aerosol)..... 0.777-0.807.
Solubility in water..... Nil.
Aerosol Flame Projection..... Not available .
Auto Ignition Temperature (Propellant), ° C.. 470.85 °C (888.5 °F) .
Flashback..... No data .
Flash Point (° C), Method..... -104 °C (-156°F).
Lower Flammable Limit (% Vol)..... 1.8.
Upper Flammable Limit (% Vol)..... 9.5.

Section 10: STABILITY AND REACTIVITY

Stability..... Stable at normal temperatures and pressures.
Incompatibility..... Strong oxidizing agents.
Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge. High temperatures may cause
thermal decomposition.
Hazardous Products of Decomposition..... May form carbon dioxide and carbon monoxide, various hydrocarbons.
Hazardous Polymerization..... Will not occur.

Section 11: TOXICOLOGICAL INFORMATION

Route of Exposure..... Skin contact, Eye contact, Inhalation and Ingestion.
Effects of Acute Exposure..... This product is harmful if inhaled or swallowed. Contact with skin and eyes may cause mild
to moderate irritation and frostbite. Symptoms may include redness, pain, numbness,
prickling and itching. Inhalation of vapours causes irritation to the nose, throat and
respiratory tract, with coughing, wheezing, dizziness, headache, drowsiness, nausea and
vomiting. Inhalation of higher concentrations may result in central nervous system
depression and unconsciousness. High vapour concentrations reduce oxygen available for
breathing, resulting in asphyxiation.
Effects of Chronic Exposure..... May cause skin defatting and dermatitis. Intentional misuse by deliberately concentrating
and inhaling this product may be harmful or fatal.
Carcinogenicity of Material..... Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP.
Reproductive Effects..... No information is available, and no adverse effects are expected.
Teratogenicity..... No information is available, and no adverse effects are expected.
Mutagenicity..... No information is available, and no adverse effects are expected.
Toxicological Data

PRODUCT: Emzone G21 Corrosion Guard - 400g

CODE: 045021

Section 11: TOXICOLOGICAL INFORMATION

Ingredients	LC50	LD50
Petroleum Hydrocarbons	Not available	>5000 (mg/kg) (rat - oral), >2000 mg/kg (rat - dermal)
Propane	>800,000 ppm (15 min,Inh.rat)	Not available
Isobutane	658 mg/L (4hrs, rat)	Not available

Section 12: ECOLOGICAL INFORMATION

Environmental..... Complete information is not yet available. This product has not been tested. Based on information available on its ingredients, no adverse environmental impact is anticipated under intended use in accordance with instructions.

Section 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

Section 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... AEROSOLS, Class 2.1, UN1950.
 DOT (US-Road)..... AEROSOLS, Class 2.1, UN1950, LTD. QTY. OR ORM-D.
 IMDG (International- Marine)..... AEROSOLS, Class 2.1, UN1950.
 IATA (International- Air)..... AEROSOLS, Class 2.1, UN1950, LTD QTY.

Section 15: REGULATORY INFORMATION

Canada..... WHMIS Classification. A: Compressed gas. B5: Flammable Aerosol. D2B: Material causing other toxic Materials.
 USA..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. OSHA (29CFR 1910.1200) Classification: Compressed Gas. HIMS Classifications: see section 01.

Section 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHIMIS: Workplace Hazardous Materials Information System.

Prepared by Regulatory Affairs
 Preparation Date..... Oct28/13
 Last Revision Date Sep19/14